

Internet II

looking forward from 10 years ago

Scott Bradner
Harvard University
17 July 2006

I2 again - 1

Before

MFUG (whining in Monterey?)
IBM (bait & switch?)
MCI (cheap at half the price)
Mike Roberts (calling during dinner)

I2 again - 2

Team

Scott Bradner - Harvard University

Scott Brim - Cornell University

Steve Corbato - University of Washington

Russ Hobby - University of Calif. - Davis

David Wasley - University of California System

l2 again - 3

The Scene

Tuesday October 1st 1996

near Chicago

34 University CIOs

note: not CS folk

a few EDUCOM folk

a few geeks

l2 again - 4

What Was Said Then

“The future is not what it used to be.”

Paul Valery - french poet & critic

l2 again - 5

Internet II Introduction

Scott Bradner
Harvard University
1 October 1996

l2 again - 6

Current networking weaknesses

- 1 - existing commodity Internet is unreliable, overloaded and costly
- 2 - control-of-network support needed for advanced applications
- 3 - widely distributed high quality network needed to support distance learning

Internet II - focused on weakness number 2

12 again - 7

Technical objectives

- Maintain a common bearer service to support existing and new applications
- Move from best effort packet delivery to differentiated communications service
- Provide the capability to dynamically tailor network service characteristics to meet specific applications requirement

12 again - 8

Network Services

"on demand" configuration of services
guaranteed bounded delay
low data loss
high capacity
support for QoS protocols such as RSVP
access to underlying network technology

I2 again - 9

GigaPOPs

point of interconnection and service delivery
between
one or more institutions or consortia
ISPs
Internet II interconnection
telecommunications providers
high speed connection to institution
dynamically configured QoS
statistics collection point
1st phase - 20 to 30 GigaPOPs

I2 again - 10

GigaPOP interconnections

at least 622 Mb links between GigaPOPs

QoS-knowledgeable paths required between
GigaPOPs

vBNS could be initial interconnection network

assumes changed vBNS AUP

assumes addition of QoS protocols to vBNS

parallel test network implemented over PVCs

l2 again - 11

GigaPOP operations

redundant NOCs

collaborative management

l2 again - 12

Ad Hoc technical group

Scott Bradner - Harvard University

Scott Brim - Cornell University

Steve Corbato - University of Washington

Russ Hobby - University of Calif - Davis

David Wasley - University of California System

I2 again - 13

Background Paper

I2 again - 14

1st Came Prose

MISSION

"A broadband infrastructure for all communication applications"

OBJECTIVES

Maintain a common bearer service to support new and existing applications

Move from best effort packet delivery to a differentiated communications service

Provide the capability of selecting service characteristics to suit the application

Achieve an advanced communications infrastructure for the Research and Education community

Provide a platform for "precompetitive developmental activity"

I2 again - 15

Prose, contd.

THE NEED FOR THE NETWORK

The Higher Education community has articulated a set of advanced applications that will greatly enrich teaching, learning, collaboration and research activities. A major impediment to the realization of these applications is lack of advanced communications services in the current commodity Internet. The broad use of distance learning will require selectable quality of service and efficient "one-to-many" data transport in support of multimedia and shared information processing. Our leading edge research community needs high capacity and selectable quality of service to make effective use of national laboratories, computational facilities and large data repositories.

I2 again - 16

Prose, contd.

Medical researchers need support for remote consultation and diagnoses over highly reliable and predictable communications services. Applications have been proposed that could provide the needed wide area communications services but there is not yet a testbed in which to prove their effectiveness.

NETWORK SERVICES

Internet-II is designed to provide a variety of services "on demand" in support of advanced applications. These dynamically selectable services will include guaranteed bounded delay, low data loss, and high capacity. For example, in order to support delivery of advanced multimedia teaching materials from a digital library

I2 again - 17

Prose, contd.

repository to a dispersed audience of learners, it will be necessary for the service delivery infrastructure to support "multicast" data delivery with guaranteed upper bounds within the transport components on delay and data loss.

New protocols to enable this functionality have already been defined and will be deployed early in the Internet-II project. These protocols include the IETF defined quality of service protocols such as RSVP and RTP along with IPv6, the IETF-developed replacement for the version of IP that is in current use on the Internet. In addition, Internet-II will provide access to the underlying network infrastructure for those environments that can support that access and for those applications that can make use of specific capabilities offered by the infrastructure.

I2 again - 18

Prose, contd.

IMPLEMENTATION

At the heart of the Internet-II design is a new technology for providing advanced communications services. The technology, referred to as a GigaPOP, is a complex of technologies developed over the first decade of the Internet integrated with new technologies developed by vendors and the Internet Engineering community. The Internet-II project will demonstrate the effectiveness of this new set of technologies and services so that they can become the basis for the next generation of commercial Internet service offerings.

I2 again - 19

Prose, contd.

The GigaPOP is the point of interconnection and service delivery between one or more institutional members of the Internet-II development project and one or more service providers. Typical institutional connections will be made via ATM or SONET services at very high speeds. The fundamental advance represented by the GigaPOP architecture is the support of dynamically acquired "quality of service" in support of a broad range of new applications while maintaining a common interoperable "bearer service." Service characteristics will include end-user definable capacity as well as latency. An essential part of the Internet-II project will be to determine the incremental costs associated with support of differentiated classes of service and to develop the mechanisms to collect data about the use of these resources by individual users.

I2 again - 20

Prose, contd.

The architecture of the GigaPOP also will support service delivery to regional or state-based not-for-profit consortia such as the Virginia Educational Network, the Washington State K-20 network, or the combined University of California and California State University system. It is envisioned that 20-30 GigaPOPs nationwide will be adequate. These will be designed and managed collectively on behalf of the Internet-II project community.

I2 again - 21

Prose, contd.

Equipment comprising the GigaPOP will include:

- * One or more very high capacity advanced function packet data switch/routers capable of supporting at least OC12 (622 megabit/second) link speeds and switched data streams as well as packet data routing;
- * Switch/routers supporting Internet Protocols (both version 4 and the new version 6), advanced routing protocols such as MOSPF, and "quality of service" protocols such as RSVP;
- * SONET or ATM multiplexers to enable allocation of link capacity to different services such as highly reliable IP packet delivery, experimental testbeds for emerging protocols, or special requirements determined by new initiatives among the Internet-II member institutions;

I2 again - 22

Prose, contd.

- * Traffic measurement and related data gathering to enable project staff to define flow characteristics as part of the operational and performance monitoring of the GigaPOPs.

12 again - 23

Prose, contd.

One or more wide area communications service providers will connect to the GigaPOPs in order to provide communications paths between the nationwide set of GigaPOPs and between GigaPOPs and the established commodity Internet. Thus participating institutions would be able to acquire a wide variety of commercial as well as pre-competitive communications services over a single high capacity communications link to the nearest GigaPOP facility. In particular, to support high performance distance learning and remote collaboration initiatives, the GigaPOP architecture will facilitate local interconnectivity between the higher education community and those commercial providers offering the emerging high-bandwidth home access technologies.

12 again - 24

Prose, contd.

The most advanced applications will require a set of communications paths among the GigaPOPs that are engineered especially for the Internet-II project. It is essential that these interconnect pathways fully support the protocols and functions noted above. Recently, NSF has proposed an expanded role for its vBNS infrastructure that potentially could attach as many as 100 sites nationally to the current OC-3 backbone and could provide a deployment platform for emerging applications in support of research and collaboration. It is envisioned that the vBNS, with its proposed new capabilities, will be the initial interconnect network among the GigaPOPs. If the vBNS should prove insufficient for the full range of Internet-II requirements, commercial alternatives will be evaluated.

12 again - 25

Prose, contd.

Although direct SONET pathways might be most effective in providing the inter-GigaPOP pathways, it seems most likely that ATM-over-SONET will be the most commonly available commercial service. Because Internet-II uses virtual connections within and between the GigaPops, a test network can be implemented along side of the production network without having to duplicate facilities. This test network will be used to experiment with new capabilities of the network itself where the production network can be used to provide reliable service for proven applications as well as a platform for testing new applications.

12 again - 26

Prose, contd.

OPERATIONS

Clearly the design of the GigaPOPs must meet the requirements of very high reliability and availability. Each GigaPOP site will be physically secure and environmentally conditioned, including backup power and resistance to damage from acts of nature. Physically diverse fiber optic and wireless communications paths will maximize service robustness against the unlikely event of physical damage external to the site. In addition, the Internet-II infrastructure is designed to be secure from the threats of those who would seek to disrupt its operations.

Not all GigaPOP sites will be staffed 24 hours per day. Instead, redundant Network Operations Centers will monitor the operation of all equipment remotely via both in-band and out-of-band circuits and will dispatch problem resolution staff as needed to effect restoration of normal services.

I2 again - 27

Prose, contd.

CONCLUSION

The Internet-II architecture has been chosen to demonstrate the effectiveness of new technologies in providing the next generation communications infrastructure. The success of Internet-II will allow our higher education and research institutions to remain world leaders in the development of advanced applications of information technology.

Submitted by the ad hoc Internet-II technical committee: Scott Bradner, Scott W Brim, Steve Corbato, Russ Hobby, and David Wasley.

I2 again - 28

Announcement

I2 again - 29

INTERNET II PROJECT

SUMMARY

Building on the tremendous success of the last ten years in generalizing and adapting research Internet technology to academic needs, a number of universities (see list at end of this document) are now joining together with government and industry partners to accelerate the next stage of Internet development in academia. The Internet II project, as it is known, will bring focus, energy and resources to the development of a new family of advanced applications to meet emerging academic requirements in research, teaching and learning.

I2 again - 30

Announcement, contd.

The project will address major challenges of the next generation of university networks. First and most importantly, a leading edge network capability for the national research community will be created and sustained. For a number of years beginning in 1987, the network services of NSFnet were unequalled anywhere else. But the privatization of that network and the frequent congestion of its commercial replacement have deprived many faculty of the network capability needed to support world class research. This unintended result has had a significant negative impact on the university research community.

12 again - 31

Announcement, contd.

Second, network development efforts will be directed to enabling a new generation of applications that fully exploit the capabilities of broadband networks - media integration, interactivity, real time collaboration - to name a few. This work is essential if new priorities within higher education for support of national research objectives, distance education, lifelong learning, and related efforts are to be fulfilled.

Third, the work of the Internet II project will be integrated with ongoing efforts to improve production Internet services for all members of the academic community. A major goal of the project is to rapidly transfer new network services and applications to all levels of educational use and to the broader Internet community, both nationally and internationally.

12 again - 32

Announcement, contd.

SCOPE OF INTERNET II PROJECT

The project will be conducted in phases over the next three to five years, with initial participation expected from fifty to one hundred universities, a number of federal agencies, and many of the leading computer and telecommunications firms, including IBM, Cisco Systems, AT&T, MCI, and Sun. The overall project technical plan and architecture is contained in a companion document to this statement entitled "Internet II Architecture."

I2 again - 33

Announcement, contd.

In the initial project phase, end to end broadband network services will be established among the participating universities. On a parallel basis, applications design will commence using teams of university faculty, researchers, and industry experts. It is expected that within approximately eighteen months, "beta" versions of a number of applications will be in operation among the Internet II participating universities.

I2 again - 34

Announcement, contd.

INTERNET II PARTNERSHIP & FUNDING ARRANGEMENTS

In most respects, the partnership and funding arrangements for the Internet II project will parallel those of previous joint networking efforts, of which the NSFnet project is a very successful example. Industry partners will work with campus-based and regional university teams to create the advanced network services that are necessary to meet the requirements of broadband, networked applications. Federal R&D agencies will provide grant support in their areas of program interest, such as the NSF vBNS meritorious high performance networking initiative.

12 again - 35

Announcement, contd.

Funding for the Internet II project will include both financial and in kind services and products of various types that will be necessary for the project. Since most of the project effort will occur on or near university campuses, it is anticipated that the majority of funding from government research agencies and industry partners will be in the form of grants to the participating universities.

12 again - 36



12 again - 37